




Split Stargrip® series 3100S

Split Wedge Action Restraint
for Ductile Iron Pipe - New or Existing Installations
Patent #5,772,252



Split Stargrip® series 3100S for Ductile Iron Pipe

SUBMITTAL INFORMATION

PROJECT NAME:

ENGINEER:

CONTRACTOR:

SPEC. SECTION:



FEATURES & ADVANTAGES

- Includes Stargrip® series 3000S, Split Back-Up Ring and high strength low alloy steel double ended rods and nuts which meet the requirements of ANSI/AWWA C111/A21.11
- Minimum Safety Factor 2:1
- For use on all classes of Ductile Iron Pipe
- For new and existing pipe to pipe installations
- Pipe OD must be gauged overall to assure restraint will fit properly.
- Please refer to chart for maximum bell outside diameter for rod clearance.
- May also be used on steel pipe up to 12". For 14" and larger steel applications, contact Star Pipe.

MATERIAL SPECIFICATIONS:

- Gland: Ductile Iron per ASTM A536, Grade 65-45-12
- Wedges: Ductile Iron per ASTM A536, Grade 65-45-12 heat treated to a minimum of 370 BHN
 - ♦ Wedge Finish: Thermally cured fluoropolymer epoxy coating

GLAND FINISH OPTIONS (Please check one):

- Standard: alkyd enamel coating
- Optional: Starbond™ TGIC polyester powder coating applied by an electrostatic spray process
- Optional: Other (specify) _____

HARDWARE OPTIONS (Please check):

- Standard: Restraint rods and nuts are high strength low alloy steel manufactured in accordance with ANSI/AWWA C111/A21.11-00
- Optional: Restraint rods and nuts alloy SS 304 per ASTM F593
- Optional: Restraint rods and nuts alloy SS 316 per ASTM F593
- Optional: Restraint rods and nuts Fluoropolymer Star-Blue coated high strength low alloy steel manufactured in accordance with ANSI/AWWA C111/A21.11-00




STAR® PIPE PRODUCTS



Split Stargrip® series 3100S

Split Wedge Action Restraint
for Ductile Iron Pipe - New or Existing Installations
Patent #5,772,252

TECHNICAL INFORMATION



SPLIT STARGRIP® 3100S SPECIFICATIONS*

Please check sizes:

NOM. SIZE	MAX PRESSURE RATING (PSI)	RODS (QTY)	ROD DIA x LENGTH	MAX. BELL OD	APPROX WT. (LBS)
3	350	4	5/8 x 17	5.57	22
4	350	4	3/4 x 17	6.75	26
6	350	6	3/4 x 17	9.27	36
8	350	6	3/4 x 17	11.63	42
10	300	8	3/4 x 24	13.37	64
12	300	8	3/4 x 24	16.60	78
14	300	8	3/4 x 24	19.17	122
16	300	10	3/4 x 24	21.41	142
18	200	10	3/4 x 24	23.64	154
20	200	12	3/4 x 24	26.05	186
24	200	14	3/4 x 24	30.78	288
30	200	18	1 x 24	37.39	485
36	200	22	1 x 24	44.42	600
42	175	28	1 1/4 x 30	49.37	1242
48	175	32	1 1/4 x 30	56.25	1423

**All dimensions in inches except where indicated.*



STAR® PIPE PRODUCTS